

Safety Data Sheet

Ultra Fluid PC 1222

Version 1.1

Revision Date: 12/14/2020

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Ultra Fluid PC 1222

Recommended use of the chemical and restrictions on use

Recommended use : Industrial chemical

Manufacturer or supplier's details

Company : Univar Solutions México, S. de R.L. de C.V.
Address : Av. Xola, número 535, piso 2, Col. Del Valle Norte
 Deleg. Benito Juárez CP 03103
 Ciudad de México
 Mexico

Emergency telephone number:

Transport North America: CHEMTREC (1-800-424-9300)

CHEMTREC INTERNATIONAL Tel # 703-527-3887

SETIQ 800 00 214 00 / 55 55 59 15 88

Additional Information: : Responsible Party: Product Compliance Department
 E-Mail: SDSLA@univarsolutions.com
 SDS Requests: 55 1107 0170
 Website: www.univarsolutions.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 4

Acute toxicity (Dermal) : Category 5

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Long-term (chronic) aquatic hazard : Category 4

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H227 Combustible liquid.
 H313 May be harmful in contact with skin.
 H319 Causes serious eye irritation.
 H361 Suspected of damaging fertility or the unborn child.
 H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements : **Prevention:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read

Safety Data Sheet
Ultra Fluid PC 1222

Version 1.1

Revision Date: 12/14/2020

and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P264 Wash skin thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

P281 Use personal protective equipment as required.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

This SDS was prepared according to NOM-018-STPS-2015.**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical name	Weight percent
541-02-6	Decamethylcyclopentasiloxane	70 - 90
63148-62-9	Siloxanes and Silicones, di-Me	10 - 20
556-67-2	Cyclotetrasiloxane, 2,2,4,4,6,6,8,8-octamethyl-	1 - 5

Any concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If symptoms persist, call a physician.
Move to fresh air in case of accidental inhalation of vapours.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.

Safety Data Sheet

Ultra Fluid PC 1222

Version 1.1

Revision Date: 12/14/2020

If swallowed	Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital. Do not induce vomiting without medical advice.
Most important symptoms and effects, both acute and delayed	: None known.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO2) Alcohol-resistant foam Water spray Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Silica Carbon oxides formaldehyde
Specific extinguishing methods	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Safety Data Sheet

Ultra Fluid PC 1222

Version 1.1

Revision Date: 12/14/2020

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- | | |
|---|--|
| Advice on protection against fire and explosion | : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition. |
| Advice on safe handling | : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations. |
| Hygiene measures | : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday. |
| Conditions for safe storage | : No smoking.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards. |

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

- | | |
|--------------------------|---|
| Respiratory protection | : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. |
| Filter type | : Organic vapour type |
| Hand protection | |
| Remarks | : The suitability for a specific workplace should be discussed with the producers of the protective gloves. |
| Eye protection | : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems. |
| Skin and body protection | : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place. |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Safety Data Sheet

Ultra Fluid PC 1222

Version 1.1

Revision Date: 12/14/2020

Appearance	: liquid
Colour	: Clear, Colorless
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 76.6 °C (169.9 °F)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: 0.97 @ 20 - 25 °C (68 - 77 °F) Reference substance: (water = 1)
Density	: 0.97 g/cm ³ @ 20 - 25 °C (68 - 77 °F)
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources.
Incompatible materials	: Strong oxidizing agents

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg
Acute inhalation toxicity	: Acute toxicity estimate: > 40 mg/l Exposure time: 4 h Test atmosphere: vapour

Safety Data Sheet

Ultra Fluid PC 1222

Version 1.1

Revision Date: 12/14/2020

Acute dermal toxicity : Acute toxicity estimate: 3,244 mg/kg

Components:

541-02-6:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : (Rabbit): > 2,000 mg/kg
Assessment: The component/mixture is minimally toxic after single contact with skin.

63148-62-9:

Acute inhalation toxicity : LC50 (Rat, male and female): mg/m³ > 11.582
Assessment: The substance or mixture has no acute inhalation toxicity

556-67-2:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): 36 mg/l
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Skin corrosion/irritation

Components:

541-02-6:

Species: Rabbit

Result: No skin irritation

556-67-2:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Components:

541-02-6:

Species: Rabbit

Result: No eye irritation

63148-62-9:

Result: Irritating to eyes.

556-67-2:

Species: Rabbit

Result: No eye irritation

Safety Data Sheet

Ultra Fluid PC 1222

Version 1.1

Revision Date: 12/14/2020

Respiratory or skin sensitisation

Components:

541-02-6:

Test Type: lymph node assay

Species: Mouse

Result: Did not cause sensitisation on laboratory animals.

556-67-2:

Test Type: Maximisation Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Components:

541-02-6:

Genotoxicity in vitro : Test Type: Ames test
Species: Salmonella typhimurium
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Rat
Result: negative

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

556-67-2:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Species: Chinese hamster ovary (CHO)
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Rat
Result: negative

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Components:

541-02-6:

Carcinogenicity - Assessment : Carcinogenicity classification not possible from current data.

556-67-2:

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Components:

541-02-6:

Safety Data Sheet

Ultra Fluid PC 1222

Version 1.1

Revision Date: 12/14/2020

Effects on fertility	: Test Type: Two-generation study Species: Rat General Toxicity - Parent: NOAEL: 160 ppm General Toxicity F1: NOAEL: 160 ppm
Reproductive toxicity - Assessment	Fertility classification not possible from current data.
Teratogenicity - Assessment	: Embryotoxicity classification not possible from current data.
556-67-2:	
Effects on fertility	: Species: Rat General Toxicity - Parent: NOAEC: 300 ppm
Effects on foetal development	: Species: Rabbit General Toxicity Maternal: NOAEL: 300 ppm Teratogenicity: NOAEL: 500 ppm
Teratogenicity - Assessment	: Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

541-02-6:

Toxicity to fish	: Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	: Remarks: No data available
Toxicity to algae	: Remarks: No data available

556-67-2:

Toxicity to fish	: Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	: Remarks: No data available
Toxicity to algae	: Remarks: No data available
Chronic aquatic toxicity- Assessment	: May cause long lasting harmful effects to aquatic life.

Safety Data Sheet

Ultra Fluid PC 1222

Version 1.1

Revision Date: 12/14/2020

Persistence and degradability

Components:

541-02-6:

Biodegradability : Inoculum: activated sludge
Biodegradation: 0.14 %
Exposure time: 28 d
Remarks: Not readily biodegradable.

556-67-2:

Biodegradability : aerobic
Inoculum: activated sludge
Biodegradation: 3.7 %
Exposure time: 29 d

Bioaccumulative potential

Components:

541-02-6:

Partition coefficient: n-octanol/water : log Pow: 8.023 (25.3 °C)

556-67-2:

Partition coefficient: n-octanol/water : log Pow: 6.488 (25.1 °C)

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
May cause long lasting harmful effects to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation):

NA1993, Combustible liquid, n.o.s., (DECAMETHYLCYCLOPENTASILOXANE), CBL, III

MX-DG(Mexico Road Transportation): Not regulated as a dangerous good

Safety Data Sheet

Ultra Fluid PC 1222

Version 1.1

Revision Date: 12/14/2020

IATA (International Air Transport Association): Not regulated as a dangerous good

IMDG (International Maritime Dangerous Goods): Not regulated as a dangerous good

Special precautions for user

Not applicable

Special Notes: : The flash point for this material is greater than 100 F (38 C). Therefore, in accordance with 49 CFR 173.150(f) non-bulk containers (<450L or <119 gallon capacity) of this material may be shipped as non-regulated when transported solely by land, as long as the material is not a hazardous waste, a marine pollutant, or specifically listed as a hazardous substance.

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information

Other information : The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use.

Safety Data Sheet

Ultra Fluid PC 1222

Version 1.1

Revision Date: 12/14/2020

Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions Product Compliance Department (55 1107 0170) SDSLA@univarsolutions.com.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act

Safety Data Sheet

Ultra Fluid PC 1222

Version 1.1

Revision Date: 12/14/2020

>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50		Lethal Concentration 50%	