

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : UV-TITAN® L530

Manufacturer or supplier's details

Company name of supplier : Venator Americas LLC
Address : 10001 Woodloch Forest Drive
The Woodlands,
TX 77380
United States of America (USA)
Telephone : (001) 844 831 6720
Telefax : (001) 281 465 6731
E-mail address of person responsible for the SDS : msds@venatorcorp.com
Emergency telephone number : USA & Canada: +1-800-424-9300 Other Americas: +1-703-741-5970 [CCN 820025]

Recommended use of the chemical and restrictions on use

Recommended use : UV Filter
Colouring agent
Coatings
Restrictions on use : Do not use for cosmetics, food additives, drug additives, feed additives or permanent implant applications., Due to lack of related experience or data, the supplier cannot approve this use.

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Chemical nature : inorganic

Hazardous components

UV-TITAN® L530

Version 2.2 Revision Date: 03/15/2018 SDS Number: 400000000920 Date of last issue: 01/10/2018
Date of first issue: 01/09/2017

Chemical name	CAS-No.	Concentration (% w/w)
titanium dioxide	13463-67-7	80 - 100
silicon dioxide	7631-86-9	1 - 5
aluminium oxide	1344-28-1	1 - 5
propylidynetrimethanol	77-99-6	1 - 5
zirconium dioxide	1314-23-4	1 - 5

SECTION 4. FIRST AID MEASURES

- General advice : Do not leave the victim unattended.
Treat symptomatically.
- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off with soap and water.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Rinse mouth with water.
If conscious, make the victim drink the following:
Give small amounts of water to drink.
Do not induce vomiting without medical advice.
Consult a physician if necessary.
- Most important symptoms and effects, both acute and delayed : Dust contact with the eyes can lead to mechanical irritation.
Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough.
The product is not irritant but as with all fine powders can absorb moisture and natural oils from the surface of the skin during prolonged exposure.
Individuals with sensitive skin may experience skin drying on prolonged or repeated exposure.
- Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.
- Notes to physician : No specific measures identified.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Product is compatible with standard fire-fighting agents.

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

- | | |
|---|--|
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during firefighting | : No information available. |
| Hazardous combustion products | : No hazardous combustion products are known |
| Specific extinguishing methods | : Cool containers/tanks with water spray.
Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : No action shall be taken involving any personal risk or without suitable training.
Prevent unauthorised persons entering the zone.
Avoid dust formation.
Remove all sources of ignition.
Ventilate the area.
Avoid breathing dust.
Keep people away from and upwind of spill/leak.
Only qualified personnel equipped with suitable protective equipment may intervene.
Never return spills in original containers for re-use.
Treat recovered material as described in the section "Disposal considerations".
For disposal considerations see section 13.
The danger areas must be delimited and identified using relevant warning and safety signs. |
| Environmental precautions | : Try to prevent the material from entering drains or water courses.
If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : Clean-up methods - small spillage
Clean up promptly by sweeping or vacuum.
Keep in suitable, closed containers for disposal.

Clean-up methods - large spillage
Approach release from upwind.
Clean up promptly by sweeping or vacuum.
Avoid creating dusty conditions and prevent wind dispersal.
Keep in suitable, closed containers for disposal. |

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

SECTION 7. HANDLING AND STORAGE

Technical measures : Ensure that eyewash stations and safety showers are close to the workstation location.

Local/Total ventilation : Use only with adequate ventilation.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : For personal protection see section 8.
Avoid creating dust.
Smoking, eating and drinking should be prohibited in the application area.

Manual handling guidelines should be adhered to when handling sacks.
In the manufacture of titanium dioxide, product is packaged at temperatures of approximately 100 to 120° C (212 to 248° Fahrenheit). When pigment is shipped shortly after manufacture, it may stay hot for a very long time depending on ambient temperatures and inventory storage practices. Due to the potential of elevated pigment temperature, caution should be used while handling pigment and in solvent applications. Each work environment must be assessed to determine hazards.
Emptying of flexible intermediate bulk containers (FIBC's) can generate static electricity. Customers using FIBC's should consult leaflet "Tiotainer® Handling Guidelines".
Empty FIBC's by gravity only (do not empty pneumatically).
Remove all wrapping prior to emptying FIBC's.
In all cases, the protective cover or wrapping should remain in place during storage and only be removed immediately prior to use.
Care should be taken to avoid moisture, particularly with a partly used pallet of material.
When transferring from one container to another apply earthing measures and use conductive hose material.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

Smoking, eating and drinking should be prohibited in the application area.
Wash face, hands and any exposed skin thoroughly after handling.
Remove contaminated clothing and protective equipment before entering eating areas.
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.
Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in accordance with the particular national regulations.
Keep only in the original container in a cool, well ventilated place away from oxidizing agents.

UV-TITAN® L530

Version 2.2 Revision Date: 03/15/2018 SDS Number: 400000000920 Date of last issue: 01/10/2018
 Date of first issue: 01/09/2017

Keep in a dry place.
 Keep cool. Protect from sunlight.
 Eliminate all ignition sources if safe to do so.
 Keep container closed when not in use.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Use appropriate container to avoid environmental contamination.
 When using standard pallets, those containing paper or plastics bags can be stacked to a maximum of 2 high.

Materials to avoid : No materials to be especially mentioned.

Further information on storage stability : Keep in a dry place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
titanium dioxide	13463-67-7	LMPE-PPT	10 mg/m3 (Titanium)	MX OEL
		LMPE-CT	20 mg/m3 (Titanium)	MX OEL
		VLE-PPT	10 mg/m3	NOM-010-STPS-2014
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
silicon dioxide	7631-86-9	LMPE-PPT (Inhalable particles)	10 mg/m3 (Silica)	MX OEL
		LMPE-PPT (as respirable particles)	3 mg/m3 (Silica)	MX OEL
aluminium oxide	1344-28-1	LMPE-PPT	10 mg/m3	MX OEL
		VLE-PPT	10 mg/m3	NOM-010-STPS-2014
		TWA (Respirable fraction)	1 mg/m3 (Aluminium)	ACGIH
zirconium dioxide	1314-23-4	LMPE-PPT	5 mg/m3 (Zirconium)	MX OEL
		LMPE-CT	10 mg/m3 (Zirconium)	MX OEL
		VLE-PPT	5 mg/m3 (Zirconium)	NOM-010-STPS-2014
		VLE-CT	10 mg/m3 (Zirconium)	NOM-010-STPS-2014
		TWA	5 mg/m3	ACGIH

UV-TITAN® L530

Version 2.2 Revision Date: 03/15/2018 SDS Number: 400000000920 Date of last issue: 01/10/2018
 Date of first issue: 01/09/2017

			(Zirconium)	
		STEL	10 mg/m ³ (Zirconium)	ACGIH

Engineering measures : Ensure adequate ventilation, especially in confined areas.
 Use engineering controls to keep exposures below the OEL or DNEL

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines

Filter type : P2 filter

Hand protection
 Directive : Use gloves approved to relevant standards e.g. EN 374 (Europe), F739 (US).

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
 Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Protective measures : Wear suitable protective equipment.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Colour : white

Odour : none

Odour Threshold : Not relevant

pH : Measured 6 - 9

Melting point/range : > 1,800 °C

: Not applicable

Flash point : does not flash

Evaporation rate : No data is available on the product itself.

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

Flammability (solid, gas)	: No data is available on the product itself.
Flammability (liquids)	: No data is available on the product itself.
Upper explosion limit / Upper flammability limit	: No data is available on the product itself.
Lower explosion limit / Lower flammability limit	: No data is available on the product itself.
Vapour pressure	: Not applicable
Relative vapour density	: No data is available on the product itself.
Relative density	: No data is available on the product itself.
Density	: Measured 3.0 - 3.5 g/cm3 Skeletal density
Solubility(ies)	
Water solubility	: practically insoluble
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: Not applicable
Auto-ignition temperature	: No data is available on the product itself.
Thermal decomposition	: No data is available on the product itself.
Self-Accelerating decomposition temperature (SADT)	: No data is available on the product itself.
Viscosity	
Viscosity, kinematic	: Not applicable
Explosive properties	: Not explosive
Oxidizing properties	: No data is available on the product itself.
Molecular weight	: Calculation method 79.88 g/mol
Particle size	: No data is available on the product itself.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: Stable under recommended storage conditions. No hazards to be specially mentioned.
Conditions to avoid	: No data available

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

Incompatible materials : None known.

Hazardous decomposition products : At high temperature, decomposition products could include trace of alpha-ethyl acrolein and formaldehyde.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data is available on the product itself.

Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

titanium dioxide:

Acute inhalation toxicity : LC50 (Rat, male and female): 3.43 - 5.09 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

silicon dioxide:

Acute inhalation toxicity : LC50 (Rat, male and female): > 58.8 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

aluminium oxide:

Acute inhalation toxicity : LC50 (Rat, male and female): > 2.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity - Product : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation**Components:**

titanium dioxide:

Species: Rabbit

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

Assessment: No skin irritation
Method: OECD Test Guideline 404
Result: Normally reversible injuries

silicon dioxide:
Species: Rabbit
Assessment: No skin irritation
Method: OECD Test Guideline 404
Result: No skin irritation

aluminium oxide:
Species: Rabbit
Assessment: No skin irritation
Method: OECD Test Guideline 404
Result: No skin irritation

Serious eye damage/eye irritation**Components:**

titanium dioxide:
Species: Rabbit
Result: Normally reversible injuries
Assessment: No eye irritation
Method: OECD Test Guideline 405

silicon dioxide:
Species: Rabbit
Result: No eye irritation
Assessment: No eye irritation
Method: OECD Test Guideline 405

aluminium oxide:
Species: Rabbit
Result: No eye irritation
Assessment: No eye irritation
Method: OECD Test Guideline 405

Respiratory or skin sensitisation**Components:**

titanium dioxide:
Test Type: Local lymph node assay (LLNA)
Exposure routes: Skin
Species: Mouse
Assessment: Does not cause skin sensitisation.
Method: OECD Test Guideline 429
Result: Does not cause skin sensitisation.

Exposure routes: Skin
Species: Guinea pig
Assessment: Does not cause skin sensitisation.
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.

aluminium oxide:
Exposure routes: Skin

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

Species: Guinea pig
Result: Does not cause skin sensitisation.

propylidynetrimethanol:
Exposure routes: Skin
Species: Mouse
Method: OECD Test Guideline 429
Result: Does not cause skin sensitisation.

Components:

titanium dioxide:
Assessment: No skin irritation, No eye irritation
Does not cause skin sensitisation., Does not cause respiratory sensitisation.

Germ cell mutagenicity**Components:**

titanium dioxide:
Genotoxicity in vitro : Test Type: Ames test
Concentration: 100 - 200 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Concentration: 31 - 500 µg/L
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Concentration: 125 - 2500 µg/L
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

silicon dioxide:
Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Components:

titanium dioxide:
Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse (males)
Application Route: Inhalation

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

Exposure time: 5 consecutive days
Dose: 0.8, 7.2, and 28.5 mg/m³
Method: OECD Test Guideline 474
Result: negative

Test Type: Micronucleus test
Species: Rat (male and female)
Application Route: Oral
Exposure time: once
Dose: 500, 1000, and 2000 mg/kg bw
Method: OECD Test Guideline 474
Result: negative

silicon dioxide:
Genotoxicity in vivo

: Application Route: Inhalation
Dose: 50 mg/m³
Result: negative

Components:

titanium dioxide:

Germ cell mutagenicity-
Assessment

: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Animal testing did not show any mutagenic effects.

Germ cell mutagenicity-
Assessment

: No data available

Carcinogenicity**Components:**

titanium dioxide:

Species: Rat, (male and female)

Application Route: Oral

Exposure time: 103 weeks

Dose: 0, 25000, 50000 ppm

Frequency of Treatment: 7 days/week

NOAEL: > 50.000 ppm

Method: No information available.

Remarks: Titanium Dioxide: based on the results of chronic inhalation studies (with positive results only in a single species - rat), IARC has concluded that: "There is inadequate evidence in humans for the carcinogenicity of titanium dioxide. " but that : "There is sufficient evidence in experimental animals for carcinogenicity of titanium dioxide". IARCs overall evaluation was that "titanium dioxide is possibly carcinogenic to humans (Group 2B)."

Venator has examined all of the available animal carcinogenicity and mechanistic data together with workplace epidemiology data for titanium dioxide and concludes that the weight of scientific evidence indicates that there is no causative link between titanium dioxide exposure and cancer risk in humans and that workplace exposures in compliance with applicable exposure standards will not result in lung cancer or chronic respiratory diseases in humans.

silicon dioxide:

Species: Rat, (male and female)

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

Application Route: Oral
Exposure time: 103 weeks
Dose: 1800 - 3200 mg/kg
Frequency of Treatment: 7 daily
Method: OECD Test Guideline 453
Result: negative

Components:

titanium dioxide:
Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Reproductive toxicity**Components:**

aluminium oxide:
Effects on fertility : Species: Rat, male and female
Application Route: Oral
Dose: 1000 milligram per kilogram
Method: OECD Test Guideline 422
Result: Animal testing did not show any effects on fertility.

propylidynetrimethanol:

Species: Rat, male and female
Application Route: Oral
Method: OECD Test Guideline 422

Components:

titanium dioxide:
Effects on foetal development : Species: Rat, male and female
Application Route: Oral
Dose: 100, 300, and 1000 mg/kg bw/
Duration of Single Treatment: 20 d
Frequency of Treatment: 7 days/week
General Toxicity Maternal: No observed adverse effect level:
1,000 mg/kg body weight
Developmental Toxicity: No observed adverse effect level:
1,000 mg/kg body weight
Method: OECD Test Guideline 414
Result: No adverse effects

silicon dioxide:

Species: Mouse
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
1,340 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rabbit
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
1,600 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

Species: Rat
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
1,350 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

aluminium oxide:

Species: Rat
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
266 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

propylidynetrimethanol:

Species: Rat, male and female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
200 mg/kg body weight
Method: OECD Test Guideline 422
Result: No teratogenic effects

Components:

titanium dioxide:

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity**Components:**

titanium dioxide:

Species: Rat, male and female
: 3500 mg/m3
Application Route: Ingestion
Test atmosphere: dust/mist
Exposure time: 2 yr
Number of exposures: 5 d
Method: Chronic toxicity

Species: Rat, male and female
: 10 - 50 mg/m3
Application Route: Inhalation
Exposure time: 2 yr
Number of exposures: 6 hours/day, 5 days/week
Method: Chronic toxicity

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

silicon dioxide:
Species: Rat, male and female
: 4000 - 4500 mg/m3
Application Route: Ingestion
Test atmosphere: dust/mist
Exposure time: 13 Weeks
Number of exposures: 7 d
Method: OECD Test Guideline 413

Components:

titanium dioxide:
Repeated dose toxicity - : No skin irritation, No eye irritation
Assessment No adverse effect has been observed in chronic toxicity tests.

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information**Product:**

Remarks: No data available

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:**

titanium dioxide:

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): > 10,000 mg/l
 Exposure time: 96 h
 Test Type: semi-static test
 Test substance: Marine water
 Method: OECD Test Guideline 203

silicon dioxide:

Toxicity to fish : LL50 (Brachydanio rerio (zebrafish)): > 10,000 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 202

aluminium oxide:

Toxicity to fish : LC50 (Fish): > 50 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: Fresh water

propylidynetrimethanol:

Toxicity to fish : LC50: > 1,000 mg/l
 Exposure time: 96 h
 Test Type: semi-static test
 Method: OECD Test Guideline 203

Components:

silicon dioxide:

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): >= 1,000 mg/l
 Exposure time: 24 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 202

aluminium oxide:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h

propylidynetrimethanol:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 13,000 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: Fresh water

Components:

silicon dioxide:

Toxicity to algae : EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

Exposure time: 72 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 201

aluminium oxide:

Toxicity to algae

: IC50 (Selenastrum capricornutum (green algae)): > 100 mg/l
 Exposure time: 72 h

propylidynetrimethanol:

Toxicity to algae

: EbC50 (Selenastrum capricornutum (green algae)): > 1,000 mg/l
 Exposure time: 72 h
 Test substance: Fresh water
 Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity)

: No data available

Toxicity to fish (Chronic toxicity)

: No data available

Components:

propylidynetrimethanol:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): > 1,000 mg/l
 Exposure time: 21 d
 Test Type: static test
 Test substance: Fresh water

M-Factor (Chronic aquatic toxicity)

: No data available

Components:

propylidynetrimethanol:

Toxicity to microorganisms

: EC50: > 1,000 mg/l
 Exposure time: 3 h
 Test Type: static test
 Test substance: Fresh water
 Method: Directive 67/548/EEC, Annex V, C.11

Toxicity to soil dwelling organisms

: No data available

Components:

titanium dioxide:

Plant toxicity

: NOEC: 100,000 mg/kg
 Exposure time: 480 h

Components:

titanium dioxide:

Sediment toxicity

: (Gammarus pulex (Amphipod)): > 100000 mg/kg sediment dw
 Study: Acute
 Test Type: semi-static test

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

Water: Fresh water
Exposure duration: 28 d
Method: ASTM Method, other

(Gammarus pulex (Amphipod)): 100000 mg/kg sediment dw
Study: Chronic
Test Type: semi-static test
Water: Fresh water
Exposure duration: 28 d
Method: ASTM Method, other

(Gammarus pulex (Amphipod)): 14989 mg/kg sediment dw
Study: Acute
Test Type: semi-static test
Water: Marine water
Exposure duration: 10 d

Components:

titanium dioxide:
Toxicity to terrestrial organisms : NOEC: 10,000 mg/kg
Exposure time: 672 h

Ecotoxicology Assessment

Components:

aluminium oxide:
Acute aquatic toxicity : This product has no known ecotoxicological effects.

Components:

aluminium oxide:
Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Toxicity Data on Soil : No data available

Other organisms relevant to the environment : No data available

Persistence and degradability

Biodegradability - Product : Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

Biochemical Oxygen Demand (BOD) : No data available

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

Dissolved organic carbon (DOC) : No data available

Physico-chemical removability : No data available

Stability in water : No data available

Photodegradation : No data available

Impact on Sewage Treatment : No data available

Bioaccumulative potential**Components:**

titanium dioxide:
Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 19 - 352
Exposure time: 14 d
Test substance: Fresh water
Method: semi-static test
Remarks: Does not bioaccumulate.

propylidynetrimethanol:
Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): < 17
Exposure time: 42 d
Test substance: Marine water
Method: flow-through test
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water - Product : Remarks: Not applicable

Mobility in soil

Mobility : No data available

Components:

titanium dioxide:
Distribution among environmental compartments : Remarks: No data available
Stability in soil : No data available

Other adverse effects

Environmental fate and pathways : No data available

Results of PBT and vPvB assessment : No data available

Endocrine disrupting potential : No data available

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

Adsorbed organic bound halogens (AOX) : No data available

Hazardous to the ozone layer

Ozone-Depletion Potential : Not applicable

Additional ecological information - Product : No data available

No data available

Global warming potential (GWP) : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
This material and its container must be disposed of in a safe way.
In accordance with local and national regulations.
Dispose of wastes in an approved waste disposal facility.
If recycling is not practicable, dispose of in compliance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA**

Not regulated as dangerous goods

IMDG

Not regulated as dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**NOM-002-SCT**

Not regulated as dangerous goods

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

Special precautions for user


Not applicable

SECTION 15. REGULATORY INFORMATION**The components of this product are reported in the following inventories:**

CH INV	: On the inventory, or in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS® IV:**

HEALTH		1
FLAMMABILITY		0
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Sources of key data used to compile the Safety Data : Information taken from reference works and the literature.,
Information derived from practical experience.

UV-TITAN® L530

Version	Revision Date:	SDS Number:	Date of last issue: 01/10/2018
2.2	03/15/2018	400000000920	Date of first issue: 01/09/2017

Sheet

Revision Date : 03/15/2018

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
MX OEL	:	Mexico. Occupational Exposure Limits
NOM-010-STPS-2014	:	Mexico. Norm NOM-010-STPS-2014 on Chemicals Polluting the Work Environment - Identification, Assessment and Control - Appendix 1 Occupational Exposure Limits
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
MX OEL / LMPE-PPT	:	Time weighted average
MX OEL / LMPE-CT	:	Short term exposure limit
NOM-010-STPS-2014 / VLE- PPT	:	Time weighted average limit value
NOM-010-STPS-2014 / VLE- CT	:	Short term exposure limit value

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Venator Materials PLC or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED VENATOR EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR VENATOR PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.