

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Acrylic Thinner 22

Manufacturer or supplier's details

Company : Univar Solutions México, S. de R.L. de C.V.

Address : Av. Xola, número 535, piso 2, Col. Del Valle Norte
Deleg. Benito Juárez CP 03103
Ciudad de México
Mexico

Emergency telephone number:
Transport North America: CHEMTREC (1-800-424-9300)
CHEMTREC INTERNATIONAL Tel # 703-527-3887
SETIQ 800 00 214 00 / 55 55 59 15 88

Additional Information: : Responsible Party: Product Compliance Department
E-Mail: SDSLA@univarsolutions.com
SDS Requests: 55 1107 0170
Website: www.univarsolutions.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Acute toxicity (Dermal) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 1 (Eyes, Central nervous system)

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2 (Central nervous system, Kidney, Liver, Auditory system)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (Auditory system, Eyes)

Aspiration hazard : Category 1

Short-term (acute) aquatic hazard : Category 2

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H225 Highly flammable liquid and vapour.
- H302 + H312 + H332 Harmful if swallowed, in contact with skin or if inhaled.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H370 Causes damage to organs (Eyes, Central nervous system).
- H373 May cause damage to organs (Central nervous system, Kidney, Liver, Auditory system) through prolonged or repeated exposure.
- H373 May cause damage to organs (Auditory system, Eyes) through prolonged or repeated exposure if inhaled.
- H401 Toxic to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
- P242 Use non-sparking tools.
- P243 Take action to prevent static discharges.
- P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P311 IF exposed or concerned: Call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

This SDS was prepared according to NOM-018-STPS-2015.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical name	Weight percent
108-88-3	Toluene	50 - 70
1330-20-7	Mixed xylenes	10 - 20
67-56-1	Methanol	10 - 20
123-86-4	n-Butyl acetate	5 - 10
100-41-4	Ethylbenzene	5 - 10
108-10-1	Methyl isobutyl ketone	1 - 5
111-76-2	2-Butoxy ethanol	1 - 5

Any concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

	If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: None known.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon oxides Unburned hydrocarbons Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). formaldehyde toxic fumes Nitrogen oxides (NO _x)
Specific extinguishing methods	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.
---	---

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

- Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

108-88-3	Toluene	LMPE-PPT	50 ppm 188 mg/m3	MX OEL
		VLE-PPT	20 ppm	NOM-010-STPS-2014
		TWA	20 ppm	ACGIH
1330-20-7	Mixed xylenes	VLE-PPT	100 ppm	NOM-010-STPS-2014
		VLE-CT	150 ppm	NOM-010-STPS-2014
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
67-56-1	Methanol	LMPE-CT	250 ppm 310 mg/m3	MX OEL
		LMPE-PPT	200 ppm 260 mg/m3	MX OEL
		VLE-PPT	200 ppm	NOM-010-STPS-2014
		VLE-CT	250 ppm	NOM-010-STPS-2014
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
123-86-4	n-Butyl acetate	LMPE-PPT	150 ppm 710 mg/m3	MX OEL
		LMPE-CT	200 ppm 950 mg/m3	MX OEL
		VLE-PPT	150 ppm	NOM-010-STPS-2014
		VLE-CT	200 ppm	NOM-010-STPS-2014
		TWA	150 ppm	ACGIH
		STEL	200 ppm	ACGIH
100-41-4	Ethylbenzene	LMPE-PPT	100 ppm 435 mg/m3	MX OEL
		LMPE-CT	125 ppm 545 mg/m3	MX OEL
		VLE-PPT	20 ppm	NOM-010-STPS-2014
		TWA	20 ppm	ACGIH
108-10-1	Methyl isobutyl ketone	LMPE-PPT	50 ppm 205 mg/m3	MX OEL
		LMPE-CT	75 ppm 307 mg/m3	MX OEL
		VLE-PPT	20 ppm	NOM-010-STPS-2014
		VLE-CT	75 ppm	NOM-010-STPS-2014
		TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
111-76-2	2-Butoxy ethanol	LMPE-PPT	26 ppm 120 mg/m3	MX OEL
		LMPE-CT	75 ppm 360 mg/m3	MX OEL
		VLE-PPT	20 ppm	NOM-010-

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

				STPS-2014
		TWA	20 ppm	ACGIH

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Self-contained breathing apparatus
In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: No data available
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Freezing point	: No data available
Boiling point (Boiling point/boiling range)	: 66 - 171.2 °C (151 - 340.2 °F)
Flash point	: -18 °C (-0.40 °F)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.8 - 0.9 g/cm ³ @ 20 °C (68 °F)
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: 230 °C
Thermal decomposition	: No data available

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources.
Incompatible materials	: Acids Aldehydes Alkali metals aluminum Bases halogens hydrogen peroxide Metals Nitrogen oxides (NOx) Oxidizing agents Reducing agents strong bases

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity	: Acute toxicity estimate: 595.24 mg/kg
Acute inhalation toxicity	: Acute toxicity estimate: 12.49 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	: Acute toxicity estimate: 1,507 mg/kg

Components:

1330-20-7:

Acute inhalation toxicity	: LC50 (Rat, male): 6700 ppm Exposure time: 4 h Assessment: The component/mixture is moderately toxic after short term inhalation.
Acute dermal toxicity	: LD50 (Rabbit): 1,700 mg/kg Assessment: The component/mixture is moderately toxic after single contact with skin.

67-56-1:

Acute oral toxicity	: Assessment: The component/mixture is toxic after single ingestion.
Acute inhalation toxicity	: Assessment: The component/mixture is toxic after short term inhalation.

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

Remarks: Supporting toxicological evidence is limited for this classification. This harmonized classification will replace the indicated classification due to industry leaders and the EU Harmonized Classification (Annex VII).

Acute dermal toxicity : Assessment: The component/mixture is toxic after single contact with skin.

100-41-4:

Acute inhalation toxicity : LC50 (Rat, Male): 1432 ppm
Exposure time: 4 h
Assessment: The component/mixture is moderately toxic after short term inhalation.

108-10-1:

Acute inhalation toxicity : LC50 (Rat): 11.6 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The component/mixture is moderately toxic after short term inhalation.

111-76-2:

Acute inhalation toxicity : LC50 (Rat, male): 2.56 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The component/mixture is moderately toxic after short term inhalation.

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

108-88-3:

Species: Rabbit
Exposure time: 4 h
Result: Irritating to skin.

1330-20-7:

Species: Rabbit
Exposure time: 24 h
Result: Irritating to skin.

111-76-2:

Result: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Components:

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

108-88-3:

Species: Rabbit

Result: Irritating to eyes.

1330-20-7:

Species: Rabbit

Result: Irritating to eyes.

108-10-1:

Species: Rabbit

Result: Irritating to eyes.

111-76-2:

Species: Rabbit

Result: Irritating to eyes.

Germ cell mutagenicity

Components:

108-88-3:

Germ cell mutagenicity -
Assessment

: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Components:

108-88-3:

Carcinogenicity - Assessment

: No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Components:

108-88-3:

Effects on foetal development

: Species: Rat
Application Route: inhalation (vapour)
Dose: 0, 250, 750, 1500, 3000 ppm
Duration of Single Treatment: 10 d
Frequency of Treatment: 6 hr/day
General Toxicity Maternal: NOAEC: 750 ppm
Developmental Toxicity: NOAEC: 750 ppm
Symptoms: Maternal toxicity, Reduced body weight, Skeletal malformations

Teratogenicity - Assessment

: Some evidence of adverse effects on development, based on animal experiments.

Reproductive toxicity - Assessment

No toxicity to reproduction

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

STOT - single exposure

Components:

108-88-3:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

1330-20-7:

Assessment: May cause respiratory irritation.

67-56-1:

Target Organs: Eyes, Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

123-86-4:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

108-10-1:

Target Organs: Respiratory system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

STOT - repeated exposure

Components:

108-88-3:

Exposure routes: Inhalation

Target Organs: Auditory system, Eyes

Assessment: May cause damage to organs through prolonged or repeated exposure., The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

1330-20-7:

Target Organs: Central nervous system, Kidney, Liver

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

100-41-4:

Target Organs: Auditory system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Components:

108-88-3:

May be fatal if swallowed and enters airways.

1330-20-7:

May be fatal if swallowed and enters airways.

100-41-4:

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

108-88-3:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.5 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : LC50 (Ceriodaphnia dubia): 3.78 mg/l
Exposure time: 48 h
Test Type: Renewal

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.74 mg/l
Exposure time: 7 d

Acute aquatic toxicity- Assessment : Toxic to aquatic life.

Chronic aquatic toxicity- Assessment : Harmful to aquatic life with long lasting effects.

123-86-4:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44 mg/l
Exposure time: 48 h
Test Type: static test

Acute aquatic toxicity- Assessment : Harmful to aquatic life.

Chronic aquatic toxicity- Assessment : This product has no known ecotoxicological effects.

100-41-4:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (microalgae)): 5.4 mg/l
Exposure time: 72 h
Test Type: static test

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

Chronic aquatic toxicity- Assessment : Harmful to aquatic life with long lasting effects.

Persistence and degradability

Components:

108-88-3:

Biodegradability : aerobic
Inoculum: Sewage
Result: Readily biodegradable.
Biodegradation: 73 %
Exposure time: 5 d
Remarks: Readily biodegradable

1330-20-7:

Biodegradability : Inoculum: activated sludge
Result: Readily biodegradable.
Biodegradation: 72 %
Exposure time: 20 d

67-56-1:

Biodegradability : aerobic
Inoculum: Activated sludge, domestic, adaption not specified
Result: Readily biodegradable.
Biodegradation: 72 %

123-86-4:

Biodegradability : aerobic
Inoculum: Activated sludge, domestic, adaption not specified
Biodegradation: 83 %
Exposure time: 28 d

100-41-4:

Biodegradability : Inoculum: activated sludge
Result: Readily biodegradable.
Biodegradation: 70 %
Exposure time: 28 d

108-10-1:

Biodegradability : Inoculum: activated sludge
Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d

111-76-2:

Biodegradability : aerobic
Inoculum: Activated sludge, domestic, adaption not specified
Result: Readily biodegradable.
Biodegradation: 90.4 %
Exposure time: 28 d

Bioaccumulative potential

Components:

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

108-88-3:

Bioaccumulation : Bioconcentration factor (BCF): 90

Partition coefficient: n-octanol/water : log Pow: 2.73 (20 °C)
pH: 7**67-56-1:**Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 1.0
Exposure time: 72 d
Concentration: 5 mg/l
Remarks: This substance is not considered to be very persistent and very bioaccumulating (vPvB).**123-86-4:**Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 15**100-41-4:**Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 1
Exposure time: 6 Weeks**108-10-1:**

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Mobility in soil

No data available

Other adverse effects**Product:**Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.
Harmful to aquatic life with long lasting effects.**Components:****100-41-4:**

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methodsContaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation):

UN1993, Flammable liquids, n.o.s., (TOLUENE, MIXED XYLENES), 3, II

MX-DG (Mexico Road Transportation):

UN1993, FLAMMABLE LIQUID, N.O.S., (TOLUENE, MIXED XYLENES), 3, II

IATA (International Air Transport Association):

UN1993, FLAMMABLE LIQUID, N.O.S., (TOLUENE, MIXED XYLENES) , 3, II, Flash Point:-18 °C(-0.40 °F)

IMDG (International Maritime Dangerous Goods):

UN1993, FLAMMABLE LIQUID, N.O.S., (TOLUENE, MIXED XYLENES), 3, II

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
DSL	: not determined
AICS	: not determined
NZIoC	: not determined
ENCS	: not determined
KECI	: not determined
PICCS	: not determined
IECSC	: not determined

SECTION 16. OTHER INFORMATION

Further information

Other information : The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions Product Compliance Department (55 1107 0170) SDSLA@univarsolutions.com.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery

Safety Data Sheet

Acrylic Thinner 22

Version 1.1

Revision Date: 09/14/2021

>=	Greater Than or Equal To	STEL	Act
IC50	Inhibition Concentration 50%	SARA	Short-term Exposure Limit
IARC	International Agency for Research on Cancer	TLV	Superfund Amendments and Reauthorization Act.
IECSC	Inventory of Existing Chemical Substances in China	TWA	Threshold Limit Value
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Time Weighted Average
KECI	Korea, Existing Chemical Inventory	UVCB	Toxic Substance Control Act
<=	Less Than or Equal To	WHMIS	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
LC50		Lethal Concentration 50%	Workplace Hazardous Materials Information System