

Safety Data Sheet**BLEND THINNER LG-15 (B)**

Version 1.0

Revision Date: 03/02/2022

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**Product name** : BLEND THINNER LG-15 (B)**Recommended use of the chemical and restrictions on use**

Recommended use : Reserved for industrial and professional use.

Manufacturer or supplier's details**Company** : Univar Solutions México, S. de R.L. de C.V.
Address : Av. Xola, número 535, piso 2, Col. Del Valle Norte
Deleg. Benito Juárez CP 03103
Ciudad de México
Mexico**Emergency telephone number:**

Transport North America: CHEMTREC (1-800-424-9300)

CHEMTREC INTERNATIONAL Tel # 703-527-3887

SETIQ 800 00 214 00 / 55 55 59 15 88

Additional Information: : Responsible Party: Product Compliance Department
E-Mail: SDSLA@univarsolutions.com
SDS Requests: 55 1107 0170
Website: www.univarsolutions.com**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 3

Acute toxicity (Inhalation) : Category 3

Acute toxicity (Dermal) : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 1 (Eyes, Central nervous system)
- single exposureSpecific target organ toxicity : Category 3 (Respiratory system, Central nervous system)
- single exposureSpecific target organ toxicity : Category 2 (Central nervous system, Kidney, Liver)
- repeated exposure

Aspiration hazard : Category 1

Short-term (acute) aquatic : Category 3
hazardLong-term (chronic) aquatic : Category 3
hazard

Safety Data Sheet

BLEND THINNER LG-15 (B)

Version 1.0

Revision Date: 03/02/2022

GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: H225 Highly flammable liquid and vapour.
H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H370 Causes damage to organs (Eyes, Central nervous system).
H373 May cause damage to organs (Central nervous system, Kidney, Liver) through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P311 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Safety Data Sheet

BLEND THINNER LG-15 (B)

Version 1.0

Revision Date: 03/02/2022

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P361 + P364 Take off immediately all contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

This SDS was prepared according to NOM-018-STPS-2015.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical name	Weight percent
67-56-1	Methanol	30 - 50
1330-20-7	Mixed xylenes	20 - 30
110-54-3	Hexane	10 - 20
79-20-9	Methyl acetate	10 - 20
100-41-4	**Ethylbenzene	10 - 20
109-66-0	Pentane	5 - 10
111-76-2	2-Butoxy ethanol	1 - 5

Any concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and water.
If symptoms persist, call a physician.

Safety Data Sheet

BLEND THINNER LG-15 (B)

Version 1.0

Revision Date: 03/02/2022

In case of eye contact	: Wash contaminated clothing before re-use. : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: None known.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon oxides formaldehyde toxic fumes Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Specific extinguishing methods	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so.

Safety Data Sheet

BLEND THINNER LG-15 (B)

Version 1.0

Revision Date: 03/02/2022

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Hygiene measures : Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
67-56-1	Methanol	LMPE-CT	250 ppm 310 mg/m3	MX OEL
		LMPE-PPT	200 ppm 260 mg/m3	MX OEL

Safety Data Sheet

BLEND THINNER LG-15 (B)

Version 1.0

Revision Date: 03/02/2022

		VLE-PPT	200 ppm	NOM-010-STPS-2014
		VLE-CT	250 ppm	NOM-010-STPS-2014
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
1330-20-7	Mixed xylenes	VLE-PPT	100 ppm	NOM-010-STPS-2014
		VLE-CT	150 ppm	NOM-010-STPS-2014
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
110-54-3	Hexane	LMPE-PPT	50 ppm 176 mg/m3	MX OEL
		VLE-PPT	50 ppm	NOM-010-STPS-2014
		TWA	50 ppm	ACGIH
79-20-9	Methyl acetate	LMPE-PPT	200 ppm 610 mg/m3	MX OEL
		LMPE-CT	250 ppm 760 mg/m3	MX OEL
		VLE-PPT	200 ppm	NOM-010-STPS-2014
		VLE-CT	250 ppm	NOM-010-STPS-2014
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
100-41-4	**Ethylbenzene	LMPE-PPT	100 ppm 435 mg/m3	MX OEL
		LMPE-CT	125 ppm 545 mg/m3	MX OEL
		VLE-PPT	20 ppm	NOM-010-STPS-2014
		TWA	20 ppm	ACGIH
109-66-0	Pentane	LMPE-CT	760 ppm 2,250 mg/m3	MX OEL
		LMPE-PPT	600 ppm 1,800 mg/m3	MX OEL
		VLE-PPT	600 ppm	NOM-010-STPS-2014
111-76-2	2-Butoxy ethanol	LMPE-PPT	26 ppm 120 mg/m3	MX OEL
		LMPE-CT	75 ppm 360 mg/m3	MX OEL
		VLE-PPT	20 ppm	NOM-010-STPS-2014
		TWA	20 ppm	ACGIH

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Self-contained breathing apparatus

Safety Data Sheet

BLEND THINNER LG-15 (B)

Version 1.0

Revision Date: 03/02/2022

In the case of vapour formation use a respirator with an approved filter.	
Hand protection	
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: Characteristic
Odour	: solvent-like
Odour Threshold	: No data available
pH	: No data available
Freezing point	: No data available
Boiling point (Boiling point/boiling range)	: Estimated > 35 °C (> 95 °F)
Flash point	: -18 °C (-0.40 °F) (for a component of this mixture)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: ca. 0.785 g/cm ³ @ 20 - 25 °C (68 - 77 °F)
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reac-	: No decomposition if stored and applied as directed.

Safety Data Sheet

BLEND THINNER LG-15 (B)

Version 1.0

Revision Date: 03/02/2022

tions

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.
 Incompatible materials : Acids
 Alkali metals
 aluminum
 Bases
 Nitrogen oxides (NOx)
 Oxidizing agents
 Reducing agents

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: 292.54 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 7.11 mg/l
 Exposure time: 4 h
 Test atmosphere: vapour

Acute dermal toxicity : Acute toxicity estimate: 760.24 mg/kg

Components:

67-56-1:

Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term inhalation.
 Remarks: Supporting toxicological evidence is limited for this classification. This harmonized classification will replace the indicated classification due to industry leaders and the EU Harmonized Classification (Annex VII).

Acute dermal toxicity : Assessment: The component/mixture is toxic after single contact with skin.

1330-20-7:

Acute inhalation toxicity : LC50 (Rat, male): 6700 ppm
 Exposure time: 4 h
 Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg
 Assessment: The component/mixture is moderately toxic after single contact with skin.

111-76-2:

Safety Data Sheet

BLEND THINNER LG-15 (B)

Version 1.0

Revision Date: 03/02/2022

Acute inhalation toxicity : LC50 (Rat, male): 2.56 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The component/mixture is moderately toxic after short term inhalation.

Skin corrosion/irritation

Components:

1330-20-7:

Species: Rabbit
Exposure time: 24 h
Result: Irritating to skin.

110-54-3:

Species: Rabbit
Result: Irritating to skin.

111-76-2:

Result: Irritating to skin.

Serious eye damage/eye irritation

Components:

1330-20-7:

Species: Rabbit
Result: Irritating to eyes.

79-20-9:

Species: Rabbit
Result: Irritating to eyes.
Exposure time: 24 h

111-76-2:

Species: Rabbit
Result: Irritating to eyes.

Reproductive toxicity

Components:

110-54-3:

Effects on fertility : Species: Rat, male
Application Route: inhalation (vapour)
Frequency of Treatment: 6 days/week
General Toxicity - Parent: LOAEL: 5,000 ppm
Symptoms: Testicular effects

Effects on foetal development : Test Type: Fertility/early embryonic development
Species: Mouse
Application Route: inhalation (vapour)
Duration of Single Treatment: 12 d
Developmental Toxicity: LOAEC: 200 ppm
Result: Teratogenic potential

Safety Data Sheet

BLEND THINNER LG-15 (B)

Version 1.0

Revision Date: 03/02/2022

Reproductive toxicity - Assessment

Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

Teratogenicity - Assessment

: Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure

Components:

67-56-1:

Target Organs: Eyes, Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

1330-20-7:

Assessment: May cause respiratory irritation.

110-54-3:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

79-20-9:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

109-66-0:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Components:

1330-20-7:

Target Organs: Central nervous system, Kidney, Liver

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

110-54-3:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Components:

1330-20-7:

May be fatal if swallowed and enters airways.

Safety Data Sheet

BLEND THINNER LG-15 (B)

Version 1.0

Revision Date: 03/02/2022

110-54-3:

May be fatal if swallowed and enters airways.

109-66-0:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

110-54-3:

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): 9.285 mg/l
Exposure time: 72 h
Remarks: Modeled result from QSAR

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): 2.8 mg/l
Exposure time: 28 d
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.
Supporting toxicological evidence is limited for this classification. This harmonized classification will replace the indicated classification due to industry leaders and the EU Harmonized Classification (Annex VII).

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 4.888 mg/l
Exposure time: 21 d
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.
Supporting toxicological evidence is limited for this classification. This harmonized classification will replace the indicated classification due to industry leaders and the EU Harmonized Classification (Annex VII).

Acute aquatic toxicity- Assessment : Toxic to aquatic life.

Chronic aquatic toxicity- Assessment : Toxic to aquatic life with long lasting effects.

109-66-0:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.26 mg/l
Exposure time: 96 h
Test Type: static test

Safety Data Sheet

BLEND THINNER LG-15 (B)

Version 1.0

Revision Date: 03/02/2022

Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 2.7 mg/l Exposure time: 48 h Test Type: static test
Toxicity to algae	: EC50: 7.51 mg/l End point: Biomass Exposure time: 72 h Test Type: static test
Toxicity to fish (Chronic toxicity)	: NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated 6.165 mg/l Exposure time: 28 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOELR (Daphnia magna (Water flea)): 10.76 mg/l Exposure time: 21 d
Acute aquatic toxicity- Assessment	: Toxic to aquatic life.
Chronic aquatic toxicity- Assessment	: Toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

67-56-1:

Biodegradability	: aerobic Inoculum: Activated sludge, domestic, adaption not specified Result: Readily biodegradable. Biodegradation: 72 %
------------------	---

1330-20-7:

Biodegradability	: Inoculum: activated sludge Result: Readily biodegradable. Biodegradation: 72 % Exposure time: 20 d
------------------	---

110-54-3:

Biodegradability	: aerobic Inoculum: Activated sludge, domestic, adaption not specified Result: Readily biodegradable. Biodegradation: 98 % Exposure time: 28 d
------------------	--

79-20-9:

Biodegradability	: aerobic Inoculum: Activated sludge, domestic, non-adapted Result: Readily biodegradable. Biodegradation: 70 % Exposure time: 28 d
------------------	---

109-66-0:

Biodegradability	: aerobic Inoculum: activated sludge Result: Readily biodegradable.
------------------	---

Safety Data Sheet

BLEND THINNER LG-15 (B)

Version 1.0

Revision Date: 03/02/2022

Biodegradation: 87 %

Testing period: 7 d

Exposure time: 28 d

111-76-2:

Biodegradability

: aerobic

Inoculum: Activated sludge, domestic, adaption not specified

Result: Readily biodegradable.

Biodegradation: 90.4 %

Exposure time: 28 d

Bioaccumulative potential

Components:

67-56-1:

Bioaccumulation

: Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 1.0

Exposure time: 72 d

Concentration: 5 mg/l

Remarks: This substance is not considered to be very persistent and very bioaccumulating (vPvB).

110-54-3:

Bioaccumulation

: Bioconcentration factor (BCF): 501.18

Remarks: The substance has low potential for bioaccumulation.

109-66-0:

Bioaccumulation

: Bioconcentration factor (BCF): 171

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: The product should not be allowed to enter drains, water courses or the soil.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Send to a licensed waste management company.

Contaminated packaging

: Empty remaining contents.

Dispose of as unused product.

Safety Data Sheet**BLEND THINNER LG-15 (B)**

Version 1.0

Revision Date: 03/02/2022

Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**DOT (Department of Transportation):**

UN1993, Flammable liquids, n.o.s., (METHANOL, MIXED XYLENES), 3, II

MX-DG (Mexico Road Transportation):

UN1992, LIQUIDO INFLAMABLE, TOXICO, N.E.P., (METHANOL, MIXED XYLENES), 3 (6.1), II

IATA (International Air Transport Association):

UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S., (METHANOL, MIXED XYLENES), 3 (6.1), II, Flash Point:-18 °C(-0.40 °F)

IMDG (International Maritime Dangerous Goods):

UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S., (METHANOL, MIXED XYLENES), 3, (6.1), II

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION**The components of this product are reported in the following inventories:**

TSCA	: not determined
DSL	: not determined
AICS	: not determined
NZIoC	: not determined
ENCS	: not determined
KECI	: not determined
PICCS	: not determined
IECSC	: not determined

SECTION 16. OTHER INFORMATION**Further information**

Other information : The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which

Safety Data Sheet

BLEND THINNER LG-15 (B)

Version 1.0

Revision Date: 03/02/2022

we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions Product Compliance Department (55 1107 0170) SDSLA@univarsolutions.com.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic

Safety Data Sheet

BLEND THINNER LG-15 (B)

Version 1.0

Revision Date: 03/02/2022

GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50			Lethal Concentration 50%